\* 2b = average spacing of end post and adjacent span, with exceptions stated in Note 4.

## ELEVATION - END POST TRANSITION AREA

Scale: None

- I. Transition areas should be provided on both ends of the bridge, comprised of a tapered concrete lug and three tapered fence panels, all equally spaced.

  2. The end of the concrete lug on both the approach and trail end shall be 2'-8".
- 3. The End Post Transition Area shall always begin at the end of the end post and be laid out in accordance with the following chart.
- 4. When roadway joint falls in the middle of a tapered panel (Joint Locations B, C, and D) the first full height panel on the bridge shall be the average spacing of the panels in the transition area and the adjacent span.

## END POST TRANSITION AREA

Roadway Joint Location	End Post Length	Fence Transition Panels on End Post	Fence Transition Panels on Bridge
А	L <u>≤</u> 8′-0′′	0	3
В	8'-0'' ⟨ L· <u>⟨</u> I2'-0''	1/2	21/2
C	12'-0" < L· <u>⟨</u> 20'-0"	11/2	11/2
D	20'-0'' ⟨ L: <u>⟨</u> 28'-0''	21/2	1/2
**E	28′-0′′ ⟨ L	$3 + (n + \frac{1}{2})$ full height panels	0

\*\* Location of Bridge Expansion Joint E varies depending on the number of full height panels on the endpost.

FOR OFFICE USE ONLY

n = the number of full height panels on the end post

APPROVAL			
OFFICE OF STRUCTURES			
DATE: 6/1/05			
REVISIONS			
SHA	FHWA		
•			

FHWA APPROVAL

DATE:

STATE OF MARYLAND DEPARTMENT OF TRANSPORTATION STATE HIGHWAY ADMINISTRATION OFFICE OF STRUCTURES

LAYOUT OF FENCING ON BRIDGES

**STANDARD NO.** BR-SS(3.06)-03-78

SHEET 2 OF 2